

ELECTRIC CHAIN HOIST

Suspension Type

- Single Speed Model
- Dual Speed Model



Specifications table

SINGLE SPEED (3 PHASE)

F(H)

Rated Load (kg)		1,000	2,000	3,000	5,000	10,000	15,000	20,000
Model Name		1F(H)	2F(H)	3F(H)	5F(H)	10FH	15FH	20FH
Standard Lift (m)		3(6)				6		
Hoisting Speed (m/min)	50Hz	7.1	6.8	4.1	2.8	2.8	1.8	1.4
	60Hz	8.5	8.2	4.9	3.3	3.3	2.2	1.6
Motor Output (kW)	50Hz	1.3	2.4			2.4×2		
	60Hz	1.6	2.9			2.9×2		
Link Chain	Dia. (mm)	φ 7.1		φ 10				
	No. of Falls	1	1	2	3	4	6	8
Rating		30% ED						
Power Cord Length		5m						

DUAL SPEED (3 PHASE)

FN(H)

Rated Load (kg)	2,000	3,000	5,000	10,000	15,000
Model Name	2FN(H)	3FN(H)	5FN(H)	10FNH	15FNH
Standard Lift (m)	3(5)			6	6
Hoisting Speed (m/min)	50Hz	6.8/1.7	4.0/1.0	2.8/0.7	1.8/0.45
	60Hz	8.2/2.1	4.8/1.2	3.3/0.8	2.2/0.55
Motor Output (kW)	50Hz	2.4/0.6			2.4/0.6×2
	60Hz	2.9/0.7			2.9/0.7×2
Link Chain	Dia. (mm)	φ10			
	No. of Falls	1	2	3	4
Rating	20% ED				
Power Cord Length	5m				