

POLYPROPYLENE ROPE – 3 STRAND & 8 STRAND

Properties:

- High Breaking Strength
- Light Weight
- Controlled Elongation
- Unaffected by Acids & Alkalies
- Negligible Water absorption
- Abrasion Resistant
- U.V. Stabilized & Long lasting

Applications:

- In Fishery Industry
- For Submersible Pumps
- For Marine Purposes
- For Construction
- In Agriculture
- In Transportation

In Transportation

- Spliced with eyes
- Special lengths
- Reworked components – Metal, plastic (Eye sockets, hooks, carabiners etc)



High Strength Polypropylene Rope (Danline)		
Dia (mm)	Weight per coil of 100 Mtrs (KG)	Minimum Breaking Strength (KGF)
4	0.72	320
6	1.63	690
8	2.90	1200
10	4.53	1800
12	6.52	2600
14	8.88	3500
16	11.60	4400
18	14.70	5600
20	18.10	6800
22	21.90	8100
24	26.10	9500
26	30.60	10900
28	35.50	12500
30	40.80	14300
32	46.40	16000
36	58.70	19800

High Strength Polypropylene Rope (Danline)			
Dia (mm)	Circ (inches)	Weight per coil of 100 Mtrs (KG)	Minimum Breaking Strength (KGF)
36	4.5	59	22800
40	5	72	27900
44	5.5	88	33300
48	6	104	39300
52	6.5	122	45700
56	7	142	52400
60	7.5	163	59400
64	8	186	67000
72	9	235	83600
80	10	290	101400
88	11	351	121300
96	12	417	142700
104	13	490	165100
112	14	568	191600
120	15	652	217100