


ENDLESS ROUND SLINGS

- Endless Round Slings are made with high tenacity polyester webbing.
- Round Slings are manufactured either to EN 1492-2:2000 with Safety factor 7:1.
- Color coded and striped for WLL (Working Load Limit) Identification.
- We offer slings in MM system (i.e. 30mm, 60mm, 900mm etc.) and also in inch system (i.e. 1" 2" 3"etc)



		ROUND ENDLESS SLINGS CAPACITY IN KGS								
		WLL kg with one Round Endless Sling					WLL kg with two Round Endless Sling			
		Straight Lift	Choke Hitch	Basket Hitch up to 7° 7° - 45° 45° - 60°			Straight Inclination 7° - 45° 45° - 60°		Choke Inclination 7° - 45° 45° - 60°	
APPROX. DIA	COLOUR CODE									
Mode Factor		M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8
18	Violet	1000	800	2000	1400	1000	1400	1000	1120	800
20	Green	2000	1600	4000	2800	2000	2800	2000	2240	1600
22	Yellow	3000	2400	6000	4200	3000	4200	3000	3360	2400
25	Grey	4000	3200	8000	5600	4000	5600	4000	4480	3200
28	Red	5000	4000	1000	7000	5000	7000	5000	5600	4000
32	Brown	6000	4800	12000	8400	6000	8400	6000	6720	4800
38	Blue	8000	6400	16000	11200	8000	11200	8000	8960	6400
46	Orange	10000	8000	20000	14000	10000	14000	10000	11200	8000
58	Orange	12000	9600	24000	16800	12000	16800	12000	13440	9600
70	Orange	15000	12000	30000	21000	15000	21000	15000	16800	12000
78	Orange	20000	16000	40000	28000	20000	28000	20000	22400	16000
90	Orange	25000	20000	50000	35000	25000	35000	25000	28000	20000
100	Orange	30000	24000	60000	42000	30000	42000	30000	33600	24000
115	Orange	36000	28800	72000	50400	36000	50400	36000	40320	28800
180	Orange	50000	40000	100000	70000	50000	70000	50000	56000	40000
200	Orange	75000	60000	150000	105000	75000	105000	75000	84000	60000
250	Orange	100000	80000	200000	140000	100000	140000	100000	112000	80000