



WIRE ROPE CLIP LM 450

- Material** : Drop forged high tensile steel
Finish : Bridge - Hot dip galvanized, U-bolt – Electro plated
Standard : EN 13411-5 Type B
 Formerly U.S. Federal Specification FF-C-450D
Certificate : Manufacturer test certificate



ITEM NO.	SIZE	A	B	C	D	E	F	G
LM-WRC0216	1/8	0.22	0.72	0.44	0.47	0.41	0.81	0.94
LM-WRC0316	3/16	0.25	0.97	0.56	0.59	0.5	0.94	1.16
LM-WRC0416	1/4	0.31	1.03	0.63	0.75	0.66	1.19	1.44
LM-WRC0516	5/16	0.38	1.23	0.75	0.88	0.72	1.31	1.69
LM-WRC0616	3/8	0.44	1.5	0.75	1	0.91	1.63	1.94
LM-WRC0716	7/16	0.50	1.88	1	1.19	1.03	1.81	2.28
LM-WRC0816	1/2	0.50	1.88	1	1.19	1.13	1.91	2.28
LM-WRC0916	9/16	0.56	2.25	1.25	1.31	1.22	2.06	2.5
LM-WRC1016	5/8	0.56	2.38	1.25	1.31	1.34	2.06	2.5
LM-WRC1216	3/4	0.62	2.75	1.44	1.5	1.41	2.25	2.84
LM-WRC1416	7/8	0.75	3.12	1.62	1.75	1.49	2.44	3.16
LM-WRC1616	1	0.75	3.5	1.81	1.88	1.78	2.63	3.47
LM-WRC1816	1 1/8	0.75	3.88	2	2	1.91	2.81	3.59
LM-WRC2016	1 1/4	0.88	4.25	2.13	2.31	2.19	3.13	4.13
LM-WRC2216	1 3/8	0.88	4.53	2.31	2.38	2.31	3.13	4.19
LM-WRC02416	1 1/2	0.88	4.94	2.38	2.59	2.44	3.41	4.44
LM-WRC2616	1 5/8	1.00	5.31	2.62	2.75	2.66	3.63	4.75
LM-WRC2816	1 3/4	1.13	5.75	2.75	3.06	2.94	3.81	5.28
LM-WRC3216	2	1.25	6.44	3	3.38	3.23	4.44	5.88
LM-WRC3616	2 1/4	1.25	7.13	3.19	3.88	3.19	4.5	6.38
LM-WRC4016	2 1/2	1.25	7.69	3.44	4.13	3.69	4.05	6.63
LM-WRC4416	2 3/4	1.25	8.31	3.56	4.38	4.88	5.00	6.88
LM-WRC2816	3	1.50	9.19	3.88	4.75	4.69	5.88	7.63



*Maximum Proof Load is 2 times the Working Load Limit.

*Minimum Ultimate Strength is 6 times the Working Load Limit.