

TECHNICAL DATA SHEET

PRODUCT : TWIN RETRACTABLE BLOCK
REF. NO. : RV-ALWB-2X2

DOC. NO. : RV/TDS/ALWB/2X2

ISSUE : 01-19

REVISION : 01

DATE : 13-03-2020

CONFORMING TO EN 360:2002



Physical Parameters	General		- Robust and Durable Aluminium Casing duly powder coated. - Has a Swivel Anchorage eye at anchorage end. - Two Steel Scaffold Hook RV-SH-131 at attachment end. - Polyester webbing used.
Textile Component	Webbing	Material Width Length Breaking Strength	Polyester 25mm 2 meter each 20kN (min.)
Metallic Assembly	Steel Scaffold Hook RV-SH-131	Material Finish Breaking Strength	Alloy steel Galvanized with golden yellow/ silver/ plated 23 kN (min.)
Corrosion Resistance			Corrosion test in accordance with ISO 9227:1990-24 hours Neutral salt spray, followed by 1 hour drying No visual evidence of any corrosion.
Vital Test Compliance	Static Strength		15 kN sustained for 3 minutes without any failure.
	Dynamic Performance		100 Kg mass free fall with the breaking force of less than 6 kN and arrest distance is less than 2 meter.