

TECHNICAL DATA SHEET

PRODUCT : CONCRETE ANCHOR STRAP

REF. NO. : RV-CAS-8005

DOC. NO. : RV/TDS/CAS/8005

ISSUE : 01-19

REVISION : 01

DATE : 13-03-2020

CONFORMING TO EN 795:2012(TYPE B)



Physical Parameters	General		- Made up of 44mm wide polyester webbing. - Black thread used with green webbing. - One side textile loop and D-Ring at other end. - Available in length of 1.07 meter or as requested.
		Weight	355.0gm $\pm$ 10gm
Textile Components	Webbing	Material Width Breaking Strength	Polyester 44mm $\pm$ 1mm 25kN
	Stitching Thread	Material Color	High tenacity polyamide Black
Metallic Assembly	D-rings	Material Finish Breaking Strength	Steel Silver or golden yellow galvanized 23kN (min.)
Vital Test Compliance	Static Strength	Conformity	18 kN sustained for 3 minutes without failure
	Dynamic Strength & Integrity Test	Conformity	When tested dynamically with a rigid steel mass of 100 kg held following 3.1 m free fall, the test mass was arrested. Than it hold an increased mass of 300 kg for 3 minutes.