

TECHNICAL DATA SHEET

PRODUCT : CONCRETE ANCHOR STRAP

REF. NO. : RV-CAS-8006

DOC. NO. : RV/TDS/CAS/8006

ISSUE : 01-19

REVISION : 01

DATE : 13-03-2020

CONFORMING TO EN 795:2012(TYPE B)



Physical Parameters	General		■ Made up of 44mm wide polyester webbing. ■ Stitched with 70 mm webbing on the back for extra protection. ■ Black thread used with green webbing. ■ Has a small D ring on one side & bigger D-ring on the other. ■ Available in length of 1 m, 1.5 m, 2.0 m or as requested.
		Weight	1.0m : 340.0 gms $\pm$ 10 gm 1.5m : 410.0 gms $\pm$ 10 gm 2.0m : 480.0 gms $\pm$ 10 gm
Textile Components	Webbing	Material Width Breaking Strength	Polyester 44mm $\pm$ 1mm 25kN
	Stitching Thread	Material Color	High tenacity polyamide Black
Metallic Assembly	D-rings	Material Plating Finish	Steel Electro deposited zinc Deburred and Polished
Vital Test Compliance	Static Strength	Conformity	18 kN sustained for 3 minutes without failure
	Dynamic Strength & Integrity Test	Conformity	When tested dynamically with a rigid steel mass of 100 kg held following 3.1 m free fall, the test mass was arrested. Than it hold an increased mass of 300 kg for 3 minutes.