

TECHNICAL DATA SHEET

PRODUCT : ANCHORAGE WEBBING SLING

REF. NO. : RV-CAS-8007


DOC. NO. : RV/TDS/CAS/8007

ISSUE : 01-19

REVISION : 01

DATE : 13-03-2020

CONFORMING TO EN 795:2012(TYPE B)



Physical Parameters	General		■ Made up of 20 mm wide Polyester webbing. ■ Black thread used with yellow webbing. ■ Temporary transportable device, intended to be used by wrapping it around a suitable structure. ■ Available in length of 0.6 m, 1.0 m & 1.5 m or as requested.
		Weight	0.6 m : 90.0gms $\pm$ 10 gm 1.0 m : 140.0gms $\pm$ 10 gm 1.5m : 180.0gms $\pm$ 10 gm
Textile Components	Webbing	Material Width Breaking Strength	Polyester 20mm $\pm$ 1mm 25kN
	Thread	Color	Black thread used with Yellow webbing
Vital Test Compliance	Static Strength	Conformity	18 kN sustained for 3 minutes without failure
	Dynamic Strength & Integrity Test	Conformity	When tested dynamically with a rigid steel mass of 100 kg, the test mass was arrested. The anchor then hold an increased mass of 300 kg for 3 minutes.