

TECHNICAL DATA SHEET

**PRODUCT : WORK POSITIONING LANYARD
WITH GRIP ADJUSTER**

REF. NO. : RV-WPL-242

DOC. NO. : RV/TDS/WPL/242

ISSUE : 01-19

REVISION : 01

DATE : 07-03-2020

CONFORMING TO EN 358:1999

With Combination Certification



Physical Parameters	General		- Rope ends spliced and covered with polyethylene protective sleeve. - Abrasion resistant thimbles provided within loops. - Karabiner (RV-SL-112) provided at one end and one karabiner (RV-SL-112) equipped with Rope Grab RG 03 for attachment. - Easy adjustment by using Rope Grab - Ø14 mm three strand Polyamide Twisted rope. - Green Tracer in the rope to indicate degradation of material. - Adjustable length up to max. 2 mtr. - Rope breaking strength min. 25 kN
	Weight		1125 gms ± 10 gm
Metallic Assembly	Karabiner RV-SL-112	Material Breaking Strength Finish	Alloy steel 25 kN (Min.) Silver/Golden Yellow Galvanized
	Rope Grab	Material Plating Finish	High strength steel Zinc plated Deburred and polished
Vital Test Compliance	Static Strength	Conformity	Sustains a force of 15 kN per 3 minutes without separating, tearing or rupture of the lanyard or any element connected to it.
	Dynamic Performance	Conformity	Sustains a Free fall from 1 meter height with a test mass of 100 kg without separating, tearing or rupture of any lanyard element.